

# ZW150-6 & ZW150PL-6 SPECIFICATIONS

HITACHI

Reliable Solutions

LANDCROS

## ENGINE

Gross power (ISO 14396)	145 HP/2,000 RPM (108 kW/2,000 RPM)
Net power (ISO 9249)	142 HP/2,000 RPM (106 kW/2,000 RPM)
Make/Model	Cummins QSB4.5 diesel engine
Type	4-cycle, water-cooled, direct injection with turbocharger and air cooled intercooler
Fuel type	#2 Diesel (Requires ultra-low sulfur fuel.)
Fuel injection pump	Electronically controlled, common rail type
Governor	All speed electrical type
Cooling module type	Forced circulation type
Number of cylinders	4
Bore and stroke	4.2" x 4.9" (107mm x 124mm)
Total displacement	272 in <sup>3</sup> (4.5 liters)
Alternator	DC 24V-65A (2.64 kW)
Air cleaner	Dry type (double element) with restriction indicator
Starter motor	DC 24V-6.1 HP (4.5 kW)
Battery	(2) 12V-930 CCA (140 Ah)

## TORQUE CONVERTER AND TRANSMISSION

Transmission	Electrical-controlled 2 motor hydrostatic transmission with summation gear box, Gear box: Fixed gear ratio, powershift countershaft type
--------------	------------------------------------------------------------------------------------------------------------------------------------------

		Normal Mode	Power Mode
Speeds: Forward	1st:	4.3 MPH (7.0 km/hr)	4.3 MPH (7.0 km/hr)
	2nd:	7.2 MPH (11.5 km/hr)	7.8 MPH (12.5 km/hr)
	3rd:	12.4 MPH (20.0 km/hr)	12.4 MPH (20.0 km/hr)
	4th:	24.2 MPH (39.0 km/hr)	24.2 MPH (39.0 km/hr)
Speeds: Reverse	1st:	4.3 MPH (7.0 km/hr)	4.3 MPH (7.0 km/hr)
	2nd:	7.2 MPH (11.5 km/hr)	7.8 MPH (12.5 km/hr)
	3rd:	12.4 MPH (20.0 km/hr)	12.4 MPH (20.0 km/hr)
	4th:	24.2 MPH (39.0 km/hr)	24.2 MPH (39.0 km/hr)

## SYSTEMS REFILL CAPACITY

LOCATION	GALLONS	LITERS
Fuel tank (diesel fuel)	53	200
Engine lubricant (including oil pan)	4.2	16
Engine coolant	5.3	20
T/M	2.6	10
Axle (front/rear)	6.6/6.6	25/25
Hydraulic oil tank	25.4	96
Hydraulic system (including hydraulic tank)	39.6	150
DEF/AdBlue® tank	3.2	12

**EPA Tier 4 Final/EU Stage IV Certified**

## HYDRAULIC AND STEERING SYSTEM

Steering type	Articulated frame steering	
Steering mechanism	Hydraulic power steering unit, double-acting piston type	
ZW140-6 and ZW150-6	Lift (boom) cylinder	Two (2) double-acting piston type: 4.9" x 29.9" (125mm x 760mm)
	Tilt (bucket) cylinder	One (1) double-acting piston type: 5.9" x 19.3" (150mm x 490mm)
ZW150PL-6	Lift (boom) cylinder	Two (2) double-acting piston type: 4.9" x 29.9" (125mm x 760mm)
	Tilt (bucket) cylinder	Two (2) double-acting piston type: 4.3" x 39.6" (110mm x 1005mm)
Steering cylinder	Two (2) double-acting piston type: 2.6" x 16.5" (65mm x 419mm)	
Main oil pump	51.2 GPM/2,988 PSI @ 2,200 RPM (194 LPM/20.6 MPa @ 2,200 RPM)	
HST charging pump	14.2 GPM/355 PSI @ 2,200 RPM (53.9 LPM/2.45 MPa @ 2,200 RPM)	
Relief valve set pressure	Control	2,988 PSI, 20.6 MPa (210 kgf/cm <sup>2</sup> )
	Priority	2,843 PSI, 19.6 MPa (200 kgf/cm <sup>2</sup> )
HYDRAULIC CYCLE TIME* front end loading, Z bar linkage system		

	ZW140-6, ZW150-6	ZW150P-6L
Lifting time (at full load)	6.0 sec.	6.0 sec.
Lowering time (empty)	4.5 sec.	3.4 sec.
Bucket dumping time	1.4 sec.	3.4 sec.
TOTAL	11.9 sec.	12.8 sec.

\* Measured in accordance with SAE J732C

## AXLE SYSTEM

Drive system	4-wheel drive
Front and rear axle	Semi-floating type
Tires	20.5 R25 (L-3)
Reduction and differential gear	Two-stage reduction with limited slip differential
Final reduction gear	Inboard mounted, heavy duty planetary gear
Oscillation angle	Total 20 (+10, -10)°

## BRAKE SYSTEM

Service brakes	Inboard mounted fully hydraulic 4-wheel disc brake. Front and rear independent brake circuit.
Parking/Emergency brake	Transmission mounted, spring-applied, hydraulically-released multi wet disc

## Remarks

- Materials and specifications are subject to change without notice and without any obligation on the part of the manufacturer.
- This information, while believed to be completely reliable, is not to be taken as warranty for which we assume legal responsibility.
- Dumping clearance and reach are measured from bucket edge in accordance with SAE J732C.
- Counterweight should not be used with tire ballast.
- This specification sheet may contain attachments and optional equipment not available in your area.

Please contact your local HCMA dealer for additional information.

# SPECIFICATIONS

## ZW150-6/ZW150PL-6

### ZW150-6 BUCKET DATA

### ZW150PL-6 BUCKET DATA


		Standard Arm		High Lift Arm	Standard Arm	
		General Purpose	Material Handling	Material Handling	General Purpose	
		Straight Edge w/ Bolt-on Cutting Edge	Straight Edge w/ Bolt-on Cutting Edge	Straight Edge w/ Bolt-on Cutting Edge	Straight Edge w/ Bolt-on Cutting Edge	
						
Capacity	Heaped	yd <sup>3</sup> (m <sup>3</sup> )	3.1 (2.4)	3.5 (2.7)	3.1 (2.4)	2.8 (2.1)
	Struck	yd <sup>3</sup> (m <sup>3</sup> )	2.6 (2.0)	2.9 (2.2)	2.6 (2.0)	2.4 (1.8)
<b>A</b>	Maximum dumping clearance	ft-in (mm)	9'4" (2,845)	9'1" (2,765)	10'6" (3,205)	9'2" (2,805)
<b>B</b>	Dumping reach (to front of bucket edge or tooth)	ft-in (mm)	3'5" (1,030)	3'8" (1,105)	4' (1,220)	4'2" (1,280)
<b>C</b>	Max. hinge pin height	ft-in (mm)	12'7" (3,840)	12'7" (3,840)	13'9" (4,200)	13' (3,975)
<b>D</b>	Digging depth (with bucket level)	in (mm)	4" (95)	4" (95)	11" (280)	4" (90)
Breakout force		lbf (kN)	22,481 (100)	20,233 (90)	21,807 (97)	23,155 (103)
Bucket tilt-back angle	at ground level	degree	43°	43°	44°	43°
	<b>E</b> at carry position	degree	50°	50°	50°	50°
Overall	<b>F</b> Length	ft-in (mm)	24'4" (7,420)	24'8" (7,530)	25'9" (7,855)	25'5" (7,735)
	<b>G</b> Height (up to cab top)	ft-in (mm)	10'9" (3,265)	10'9" (3,265)	10'9" (3,265)	10'9" (3,265)
	<b>H</b> Height (bucket fully raised)	ft-in (mm)	17' (5,190)	17'2" (5,230)	18'3" (5,555)	17'7" (5,360)
	<b>I</b> Width (outside tire)	ft-in (mm)	8'2" (2,490)	8'2" (2,490)	8'2" (2,490)	8'2" (2,490)
	<b>J</b> Width (outside bucket)	ft-in (mm)	8'5" (2,560)	8'5" (2,560)	8'5" (2,560)	8'5" (2,560)
	<b>K</b> Tread	ft-in (mm)	6'4" (1,930)	6'4" (1,930)	6'4" (1,930)	6'4" (1,930)
<b>L</b> Wheel base	ft-in (mm)	9'11" (3,000)	9'11" (3,000)	9'11" (3,000)	9'11" (3,000)	
	<b>M</b> at outside of bucket	ft-in (mm)	19'6" (5,950)	19'7" (5,980)	20'2" (6,155)	19'9" (6,030)
Clearance Circle (bucket carry position)	at outside of tire	ft-in (mm)	17'7" (5,355)	17'7" (5,355)	17'7" (5,355)	16'8" (5,090)
	<b>N</b> Minimum ground clearance	in (mm)	17" (435)	17" (435)	17" (435)	17" (435)
<b>O</b>	Full articulation angle	degree	40°	40°	40°	40°
Operating weight (with ROPS cab)*		lb (kg)	27,029 (12,260)	27,117 (12,300)	27,540 (12,490)	27,010 (12,830)
Static tipping load (with ROPS cab)*	Straight	lb (kg)	22,950 (10,410)	22,619 (10,260)	18,188 (8,250)	20,128 (9,130)
	Full turn	lb (kg)	19,930 (9,040)	19,643 (8,910)	15,719 (7,130)	17,394 (7,890)

Note: All dimensions, weight and performance data based on ISO 6746-1:1987, ISO 7137:2009 and ISO 7546:1983


\*: Static tipping load and operating weight marked with\* include 20.5R25 (L-3) tires (No ballast) with lubricants, full fuel tank and operator.

Machine stability and operating weight depend on counterweight, tire size and other attachments.

### DIMENSIONS




Equipped with 20.5 R25 (L-3) tire and ROPS cab.



# SPECIFICATIONS


## ZW150-6/ZW150PL-6

### ZW150-6 FORK SPECIFICATIONS




ZW150-6		ISO (48")	416 (48")	ISO (60")	416 (60")
<b>Q</b>	Max. stacking height	ft 12'	12'1"	12'	12'1"
<b>R</b>	Height of fork at maximum reach	ft 5'7"	5'10"	5'7"	5'10"
<b>S</b>	Reach at ground level	ft 3'11"	3'8"	3'11"	3'8"
<b>T</b>	Max. reach	ft 5'7"	5'6"	5'7"	5'6"
<b>U</b>	Reach at max. stacking height	ft 3'1"	3'	3'1"	3'
Tipping load	Straight	lb 13,798	13,636	13,044	12,896
	Full turn	lb 11,961	11,821	11,308	11,180
Max. payload per EN 474-3, 80%		lb 9,569	9,457	9,046	8,944
Max. payload per EN 474-3, 60%		lb 7,177	7,092	6,785	6,708
SAE allowable load		lb 5,980	5,910	5,654	5,590
Operating weight *		lb 27,054	27,040	27,156	27,143

### ZW150-6 BUCKET SELECTION CHART




### ZW150PL-6 FORK SPECIFICATIONS



ZW150PL-6		ISO (48")
<b>Q</b>	Max. stacking height	ft 12'4"
<b>R</b>	Height of fork at maximum reach	ft 5'11"
<b>S</b>	Reach at ground level	ft 3'10"
<b>T</b>	Max. reach	ft 5'11"
<b>U</b>	Reach at max. stacking height	ft 3'2"
Static tipping load	Straight	lb 18,120
	Full 40 degree turn	lb 15,720
Max. payload per EN 474-3, 80%		lb 12,350
Max. payload per EN 474-3, 60%		lb 9,260
SAE allowable load		lb 4.0
Operating weight *		lb 28,440

### ZW150PL-6 BUCKET SELECTION CHART



### ZW150-6 AND ZW150PL-6 WEIGHTS AND DIMENSIONS

	Operating Weight	Tipping Load			Overall Width (Outside Tire)	Overall Height	Overall Length
		Straight	Full Turn				
Belly guard	lb (kg) +150 (70)	+70 (30)	+110 (50)	+90 (40)	in (mm)		
Tires: 20.5-25-12PR (L2)	lb (kg) -400 (-180)	-260 (-120)	-240 (-110)		in (mm) -3.3 (-85)	-2.4 (-60)	+2.0 (+50)
20.5-25-12PR (L3)	lb (kg) -400 (-180)	-260 (-120)	-240 (-110)		in (mm) +0.6 (+15)	+1.2 (+30)	-1.0 (-25)
Emergency steering (Secondary steering)	lb (kg) +80 (+35)	+0 (+0)	+0 (+0)		in (mm)		
Full covered rear fender	lb (kg) +70 (+30)	+0 (+0)	+0 (+0)		in (mm)		
Bracket for rotating beacon	lb (kg) +20 (+10)	+0 (+0)	+0 (+0)		in (mm)		

\* Specs highlighted in orange denote Canada only. Note: All dimensions, weight and performance data based on ISO 6746-1:1987, ISO 7131:2009 and ISO 7546:1983  
 \* Static tipping load and operating weight include 20.5R25 (L3) tires, ROPS cabin and ride control. Machine stability and operating weight depend on counterweight, tire size and other attachments.

# EQUIPMENT DATA

## ZW150-6

### STANDARD EQUIPMENT

#### ENGINE

Air cleaner, double element  
Auto idle shut down  
Cold start (glow plug)  
Cooling fan, automatic reversible  
Cummins QSB4.5 diesel engine  
EGR system  
Fuel filter (main), w/water separator  
Fuel pre-filter, w/water separator  
Pre-cleaner (SyKlone)  
SCR catalyst and DOC  
VGT (Variable Geometry Turbocharger)  
Work mode selector

#### POWERTRAIN

Brakes, service  
Enclosed wet disc  
Dual system  
Inboard mounted  
Brake, parking  
Spring applied  
Oil pressure released  
Wet disc type  
Cooling system cores, wide-fin  
Differential, limited slip (F/R)  
Drive shafts, low maintenance  
F-R direction selector (2-column mounted/HYD-control lever mounted)  
Hydrostatic transmission  
Inching pedal  
Maximum speed adjuster for 1st speed  
Traction control  
Universal joints, sealed

#### HYDRAULIC SYSTEM

Boom kick-out, dual (operator adjustable in cab)  
Bucket positioner  
Quick coupler control lines and controls  
Control Lever, single, pilot-assisted w/1 aux Lever for 3rd spool control  
Control lever lock (electric)  
Control valve, 3-function, parallel control  
Pump, gear, fixed displacement  
Quick coupler control lines and controls  
Ride control w/load sensing valve and automatic shut-off  
Steering, orbitrol

#### QUICK LINKS

Website's  
Product Page



#### ELECTRICAL

24-volt electrical system  
Back-up alarm  
Batteries (2), 12V, 930 CCA  
Battery disconnect switch  
Converter  
Horn, dual electric  
Instrument panel, LCD, monochrome  
Lights:  
2 Headlights (halogen)  
4 Forward working lights (LED)  
4 Rear working lights (LED)  
2 Stop/tail/backup (LED)  
Turn signal w/4-way flashers/marker

#### CAB

ROPS cab: Enclosed cab with sound suppression, front & rear wipers and washers, two rear view and side mirrors, tinted glass, full view latch-back doors, sliding side windows.  
Accessory outlet, 12V,  
Adjustable armrest/console  
Air conditioner/heater/pressurizer  
AM/FM/WB radio with AUX input and Bluetooth  
Ashtray  
Cab dome lamps (2)  
Cigarette lighter  
Coat hook  
Cooler box storage area  
Cup holder (2)  
Floor mat  
Retractable seat belt (3 inch)  
ROPS/FOPS certified, ISO 3449 Level II compliance  
Seat, premium, heated w/TLV suspension  
Steering column, telescoping and tilting w/quick-release pedal  
Storage box (heated/cooled)  
Sun visor

#### OTHERS

Articulation locking bar  
Counterweight  
Drawbar  
Fire extinguisher, 5 lb., 2a:10b:c ratd (w/mounting) (US market only)  
Global e-Service, telematic monitoring system  
Ladders, inclined  
Lifting eyes  
Linkage pins, HN bushing  
Neutral safety start  
Rear grill, steel  
Steps, rear  
Vandalism protection  
Z-bar loader linkage

#### ALARMS, GAUGES, INDICATORS

Alarms (visual & audible)  
Brake oil low pressure  
Engine oil low pressure  
Hydraulic oil level  
Overheat (engine coolant)  
Steering oil low pressure  
Gauges  
DEF/AdBlue® Level  
Engine coolant temperature  
Fuel gauge  
HST oil temperature  
Indicators  
Aftertreatment Device  
Air cleaner element  
Air conditioner display  
Battery discharge warning  
Cold start  
Control lever lock  
Eco-operating status  
Emergency steering  
Engine warning  
Fan reverse rotation  
F-N-R selection  
F-N-R switch enable  
Fuel filter (plugged filter)  
Fuel filter (water in fuel)  
High beam  
HST oil temperature  
HST warning  
Maintenance  
Operating mode (Normal, Power)  
Parking brake  
Ride control  
Service  
Speedometer  
Time/operating hour/ODO  
Traction control switch  
Turn signal w/4-way flashers/marker  
Work light

#### OPTIONAL EQUIPMENT

Belly guard, front chassis, transmission (rear)  
Bolt-on cutting edges  
Camera, rear view  
Cooling cores, standard spacing (high ambient)  
Dual lever hydraulic control  
Emergency steering system  
Front and full covered rear fenders with mud flaps (20.5 Tire)  
Front and half covered rear fenders with mud flaps (20.5 Tire)  
High lift arm  
Mirror, heated rear view (outside)  
Mount bracket, wiring harness and switch for rotating lamp (without beacon) (Canada Only)  
Quick coupler & attachments

Standard and optional equipment may vary by country, so please consult your local Hitachi Construction Machinery authorized dealer for details.

Hitachi Construction Machinery Americas reserves the right to change specifications at any time without prior notification. © 2025 All Rights Reserved

# EQUIPMENT DATA

## ZW150PL-6

### STANDARD EQUIPMENT

#### ENGINE

Air cleaner, double element
Auto idle shut down
Cold start (glow plug)
Cooling fan, automatic reversible
Cummins QSB4.5
EGR system
Fuel filter (main), w/water separator
Fuel pre-filter, w/water separator
Pre-cleaner (SyKlone)
SCR system
VGT (Variable Geometry Turbocharger)
Work mode selector

#### POWERTRAIN

Brakes, service
Enclosed wet disc
Dual system
Inboard mounted
Brake, parking
Spring applied
Oil pressure released
Wet disc type
Coolers, wide fin spacing
Differential, limited slip (F/R)
Drive shafts, low maintenance
F-R direction selector (2-column mounted/HYD-control lever mounted)
Hydrostatic transmission
Inching pedal
Maximum speed adjuster for 1st speed
Traction control
Universal joints, sealed

#### HYDRAULIC SYSTEM

Boom kick-out, dual (operator adjustable in cab)
Bucket positioner
Control Lever, single, pilot-assisted w/1 aux lever for 3rd spool control
Control lever lock (electric)
Control valve, 3-function, parallel control
Pump, gear, fixed displacement
Quick Coupler Control Lines and Controls
Ride Control w/Load sensing valve and automatic shut-off
Steering, orbital

#### QUICK LINKS

Website's  
Product Page



#### ELECTRICAL

24-volt electrical system
Back-up alarm
Batteries (2), 12V, 930 CCA
Battery disconnect switch
Converter
Horn, dual electric
Instrument panel, LCD, monochrome
Lights:
2 Headlights (halogen)
4 Forward working lights (LED)
4 Rear working lights (LED)
2 Stop/tail/backup (LED)
Turn signal w/4-way flashers/marker

#### CAB

ROPS cab: Enclosed cab with sound suppression, front & rear wipers and washers, two rear view and side mirrors, tinted glass, full view latch-back doors, sliding side windows.
Accessory outlet, 12V,
Adjustable armrest/console
Air conditioner/heater/pressurizer
AM/FM/WB radio with AUX input and Bluetooth
Ashtray
Cab dome lamps (2)
Cigarette lighter
Coat hook
Cooler box storage area
Cup holder (2)
Floor mat
Retractable seat belt (3 inch)
ROPS/FOPS certified, ISO 3449 Level II compliance
Seat, premium, heated w/TLV suspension
Steering column, telescoping and tilting w/quick-release pedal
Storage box (heated/cooled)
Sun visor

#### OTHERS

Articulation locking bar
Counterweight
Drawbar
Fire extinguisher, 5 lb., 2a:10b:c ratd (w/mounting) (US market only)
Global e-Service, telematic monitoring system
Ladders, inclined
Lifting eyes
Linkage, parallel, sealed
Linkage pins, HN bushing
Neutral safety start
Rear grill, steel
Steps, rear
Vandalism protection
Quick coupler

#### ALARMS, GAUGES, INDICATORS

Alarms (visual & audible)	Brake oil low pressure
	Engine oil low pressure
	Hydraulic oil level
	Overheat (engine coolant)
	Steering oil low pressure
Gauges	DEF/AdBlue® Level
	Engine coolant temperature
	Fuel gauge
	HST oil temperature
Indicators	Aftertreatment device
	Air cleaner element
	Air conditioner display
	Battery discharge warning
	Cold start
	Control lever lock
	Eco-operating status
	Emergency steering
	Engine warning
	Fan reverse rotation
	F-N-R selection
	F-N-R switch enable
	Fuel filter (plugged filter)
	Fuel filter (water in fuel)
	High beam
	HST oil temperature
	HST warning
	Maintenance
	Operating mode (Normal, Power)
	Parking brake
	Service
	Speedometer
	Time/operating hour/ODO
	Traction control switch
	Turn signal w/4-way flashers/marker
	Work light

#### OPTIONAL EQUIPMENT

Belly guard, front chassis, transmission (rear)
Bolt-on cutting edges
Camera, rear view
Cooling cores, standard spacing (high ambient)
Dual lever hydraulic control
Emergency steering system
Front and full covered rear fenders with mud flaps (20.5 Tire)
Front and half covered rear fenders with mud flaps (20.5 Tire)
High lift arm
Mirror, heated rear view (outside)
Mount bracket, wiring harness and switch for rotating lamp (without beacon) (Canada Only)
Quick coupler & attachments

Standard and optional equipment may vary by country, so please consult your local Hitachi Construction Machinery authorized dealer for details.

Hitachi Construction Machinery Americas reserves the right to change specifications at any time without prior notification. © 2025 All Rights Reserved

10/2025 © 2025 All Rights Reserved  
Global Pub#: KL-EN252NA-US  
Printed in the USA